



US006414927B1

(12) **United States Patent**
Ota

(10) **Patent No.:** **US 6,414,927 B1**
(45) **Date of Patent:** **Jul. 2, 2002**

(54) **DISK LOADING APPARATUS**

(75) **Inventor:** Hidehiko Ota, Ehime (JP)

(73) **Assignee:** Matsushita Electric Industrial Co.,
Ltd., Osaka (JP)

(*) **Notice:** Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

(21) **Appl. No.:** 09/787,756

(22) **PCT Filed:** Aug. 17, 2000

(86) **PCT No.:** PCT/JP00/05492

§ 371 (c)(1),
(2), (4) **Date:** May 22, 2001

(87) **PCT Pub. No.:** WO01/15158

PCT Pub. Date: Jan. 3, 2001

(30) **Foreign Application Priority Data**

Aug. 19, 1999 (JP) 11-232932

(51) **Int. Cl.⁷** G11B 3/90

(52) **U.S. Cl.** 369/53.41; 369/53.43

(58) **Field of Search** 369/53.2, 53.3,
369/53.41, 53.43, 75.1, 76, 77.1, 75.2

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,719,844 A * 2/1998 Abe 369/77.1
5,828,641 A * 10/1998 Abe et al. 369/75.1

FOREIGN PATENT DOCUMENTS

JP 10-116459 5/1998
JP 2000-315349 11/2000

* cited by examiner

Primary Examiner—Paul W. Huber

(74) *Attorney, Agent, or Firm*—McDermott, Will & Emery

(57) **ABSTRACT**

A disk loading apparatus is provided which stops disks, even if the disks have different diameters, when disk center holes have been ejected to the substantially same positions out of an apparatus body during the ejection. The disks can be pulled out without soiling a recording surface of the disk. One disk-pass detecting switch detects a pass of the last end of each disk and discriminates sizes of the disks. In addition, a rotation time of a roller after the detection of the pass is controlled depending on disk diameters.

7 Claims, 3 Drawing Sheets

